





## Vertical sliding double hung window Residential 2 pane

## Features:

Sashless panes of glass move within their own plane

Provides high and low ventilation

Narrow aluminium profiles

Fits most aluminium frame profiles

Can be retrofitted to solve ventilation problems

Removable midseal closes off winter draughts

Acrylic lifting handle may be positioned at the bottom or top of the bottom sliding pane (shown at top)

Lock open position provides secure ventilation Available with or without a Base Pane

## Specifications:

Curved and/or raking heads available

Frame height from 600mm

Frame width from 370mm

Annealed, laminated, toughened or Low E glass available as standard Most powder coated and anodised aluminium finishes available as standard

 Shugg Lock - typically
 Shugg Lock - typically

 Guide N1389
 Guide N1389

 Guide N1389
 Guide N1389

Neotechnical Industries Ltd	Frame Type	APL 100mm Shop front	Drawing name	DH102_RA10 Scale	1:2
9 McDonald St, Sandringham, Auckland. Phone: 09 815 0481 Email: info@shugg.co.nz www.shugg.co.nz	Section	A:A & B:B	Date drawn	11-08-21 Revision	001
	Notes	-	Window style	Double Hung	
	Notes	-	Window format	Residential	
	Notes	-	Glazing	Single Thickness	8mm

Details subject to change without notice. Exterior frames by others, Neotechnical Industries Ltd does not own the rights to exterior frames shown and are indicative only. All other details © Neotechnical Industries Ltd, not to be reproduced, altered or distributed in any form without permission.